



NOTES:

1. FOR USE WITH TRIBUTARY DRAINAGE AREA OF LESS THAN 10 ACRES. IF DRAINAGE AREA EXCEEDS 10 ACRES, CONSULT THE DAM SAFETY SECTION OF THE WASHINGTON DEPARTMENT OF ECOLOGY MANUAL.
2. PROVIDE BAFFLES TO PREVENT SHORT-CIRCUITING.
3. SPILLWAY SHALL BE LINED WITH 2"-4" ROCKS.
4. ALL INLETS AND OUTLETS SHALL BE PROTECTED WITH RIP-RAP.
5. IF POND POSES A SAFETY HAZARD, IT SHALL BE FENCED.
6. REMOVE SEDIMENT BEFORE 1.5" ACCUMULATES.
7. PERFORATED PIPE TRENCH SHALL BE COMPLETELY LINED WITH FILTER FABRIC.
8. SEE APPLICABLE NOTES ON STD. DETAIL E8.

NO.	REVISIONS	DATE	BY

DWG: E8a.DWG



Department of
Public Works
CLARK COUNTY
WASHINGTON
proud past, promising future

TEMPORARY SEDIMENT POND

Peter Capen
COUNTY ENGINEER

APPROVED

5/23/08
DATE

STANDARD
E8a
DETAIL
DESIGNED
DRAWN
DATE 05/23/08